



Acoustic Technologies Electronics Pty Ltd

ABN 40 010 627 997

8-10 Staple Street
Seventeen Mile Rocks
Qld 4073 Australia

Telephone (617) 3376 4122
Fax (617) 3376 5793

PO Box 107
Sumner Park Qld 4074 Australia

Email info@atprofessional.com.au
Internet www.atprofessional.com.au

SFM24 Wedge Factory Settings

Optimised for Vocal Foldback

23/11/06

Active Settings

LOW SECTION Loudspeaker Management Settings

Output Gain: +0 dB
Time Delay: 0.217 mSec
Phase: Normal

High Pass Filter Frequency: 80 Hz
High Pass Filter Type: 24 dB/Octave Linkwitz Riley (6dB Butterworth)

Low Pass Filter Frequency: 1.2 kHz
Low Pass Filter Type: 24 dB/Octave Linkwitz Riley (6dB Butterworth)

Bandpass Filter #1 Frequency: 120 Hz
Bandpass Filter #1 Q: 0.71 Octaves (2)
Bandpass Filter #1 Gain: +6 dB

Bandpass Filter #2 Frequency: 900 Hz
Bandpass Filter #2 Q: 0.48 Octaves (3)
Bandpass Filter #2 Gain: -2.5 dB

HIGH SECTION Loudspeaker Management System Settings.

Output Gain: -6.5 dB
Time Delay: 0 mSec
Phase: Normal

High Pass Filter Frequency: 1.4 kHz
High Pass Filter Type: 18 dB/Octave Butterworth

Bandpass Filter #1 Frequency: 12 kHz
Bandpass Filter #1 Q: 0.71 Octaves (2)
Bandpass Filter #1 Gain: +5.0 dB