



Acoustic Technologies Electronics Pty Ltd

ABN 40 010 627 997

8-10 Staple Street
Seventeen Mile Rocks
Qld 4073 Australia

Telephone (617) 3376 4122
Fax (617) 3376 5793

PO Box 107
Sumner Park Qld 4074 Australia

Email info@atprofessional.com.au
Internet www.atprofessional.com.au

Revision Date: 25/9/06

SS24 Factory Recommended Settings

LOW SECTION Loudspeaker Management Settings

Output Gain:	+0 dB
Time Delay:	0.583 mSec
Phase:	Normal
High Pass Filter Frequency:	50 Hz
High Pass Filter Type:	24 dB/Octave Linkwitz Riley (6dB Butterworth)
Low Pass Filter Frequency:	1.41 kHz
Low Pass Filter Type:	24 dB/Octave Linkwitz Riley (6dB Butterworth)
Bandpass Filter #1 Frequency:	69.4 Hz
Bandpass Filter #1 Q:	1.150 Octaves (Q= 1.22)
Bandpass Filter #1 Gain:	+6 dB
Bandpass Filter #2 Frequency:	637 Hz
Bandpass Filter #2 Q:	0.55 Octaves (Q= 2.61)
Bandpass Filter #2 Gain:	-5.0 dB
Bandpass Filter #3 Frequency:	406 Hz
Bandpass Filter #3 Q:	0.15 Octaves (Q= 9.61)
Bandpass Filter #3 Gain:	+1.5 dB
Bandpass Filter #4 Frequency:	1.1 kHz
Bandpass Filter #4 Q:	0.5 Octaves (Q= 2.87)
Bandpass Filter #4 Gain:	-3.0 dB

SS24 Factory Recommended Settings

HIGH SECTION Loudspeaker Management System Settings.

Output Gain:	-4.5 dB
Time Delay:	0 mSec
Phase:	Invert
High Pass Filter Frequency:	1.8 kHz
High Pass Filter Type:	18 dB/Octave Butterworth
Bandpass Filter #1 Frequency:	13.7 kHz
Bandpass Filter #1 Q:	0.3 Octaves (Q= 4.8)
Bandpass Filter #1 Gain:	+6.0 dB
Bandpass Filter #2 Frequency:	1.68 kHz
Bandpass Filter #2 Q:	0.25 Octaves (Q= 5.76)
Bandpass Filter #2 Gain:	-3.0 dB
Bandpass Filter #3 Frequency:	3.24 kHz
Bandpass Filter #3 Q:	0.25 Octaves (Q= 5.76)
Bandpass Filter #3 Gain:	-2.0 dB